


>



Model Number: SC40V

Sirocco SC40V 40in Triple-Wide Vacuuming Surface Cleaner (Factory needs 2 - 4 week build time)

Manufacturer: Sirocco

Sirocco SC40V 40in Triple-Wide Vacuuming Surface Cleaner (Factory needs 2 - 4 week build time)

**** THERE ARE NO RETURNS ON THIS ITEM! ALL SALES FINAL! ****

Description

Eliminate over-spray while pressure washing shopping centers, flat-work, warehouse floors, tile surfaces, etc. production style! Sanitize with up to 250°F at 20,000 to 40,000 sq ft. per hour, and have dry floors in minutes! Crazy fast work speed – great for compelling demonstrations!

The MOST important reason to own one of these is “instant-capture” for controlling over-spray, but when you see your “quality of clean” improve too, don’t be surprised. The vacuum draws the water away from the spray area, removing the water-puddle, thus allowing better spray-impact and a faster-spinning spray-bar.

When the pressure washing and wash water control are done simultaneously, there’s NO rinsing required – and the net increase in work-speed quickly pays for the equipment!

Features

- Triple-wide 40" vacuuming deck
- Powerful 2-armed spray bars for applications requiring up to 10 gpm, includes 25° spray nozzles and hi-volume connect hose.
 - use 2-armed spray bars with higher temp (up to 250°F) and reduced flow applications, as with interior cleaning where maximum capture is required.
- Uses 1/4" MPT nozzles
- Includes 3 DYC height-adjustable swivels
- Nozzle size available in #1.5
- Triple rear vacuum ports (for reclaiming in forward motion)
- Inner and outer skirts (for preventing over-spray)
- Dual inlets for multiple machine feed, each with high-pressure filters (to insure clean spray nozzles)
 - Dual high-pressure connect hoses
 - 1:3 Vacuum hose manifold with 3ea. vacuum connect hoses
 - 4ea. height adjustable 4" caster wheels
 - Includes partial mounting hardware with 2ea. 18" attaching arms
 - Use as trailing arms for mounting underneath mower. This surface cleaner was built to be or use as trailing arms when mounting underneath mower.
 - Use as extension arms when mounting in the front of the mower. This surface cleaner was built to be mounted under a mower, so if it's mounted to the front the driver must be extra cautious during operation, especially on uneven surfaces.

Specifications

- Max PSI: 5000

>

- Max GPM: 20+ (12 to 16 gpm is best for 98% capture)
- Max Temp: 250°F
- Deck Diameter: 40"
- Requires 350-650 CFM

Notes

- Pictured with push bars, available for additional \$199
- This is for forward motion reclaim only, because of this it requires less CFM than a surface cleaner that reclaims in both forward and reverse directions. It's also lighter weight and more compact (fewer hoses, etc.).
 - Keep in mind, the larger the surface cleaner deck, the more it will dislike uneven surfaces! Plan accordingly! Surface cleaners work BEST on FLAT surfaces!
 - Lower flow and higher temperatures are MUCH easier to reclaim with, and is recommended for 98% instant capture.

https://pressurewasher.net/products/40-vacuuming-surface-cleaner?_pos=2&_sid=142025680&_ss=r&variant=13466204897315

-->

Availability: This product was added to our catalog on Wednesday 29 November, 2017