

>



Model Number: 215-CP45 PTI CH

CleanCo Truckmount 215-CP45 PTI CH For Chevy Vans Post Thermal Increase 230 degrees

Manufacturer: Esteam Cleaning Systems

CleanCo Truckmount 215-CP45 PTI CH For Chevy Vans.

Includes Dealer or Factory labor but excludes van and shipping

Compact 45 - Easy to Use Cleaning Equipment

Complete truckmount operation starts with the precisely designed control panel featuring a gauge monitoring package, pressure & temperature controls and a dual speed setting for upholstery, carpet or hard surface cleaning. Truckmount operation is powered by an E.T.M. (Electronic Throttle Module) which maintains the van engine speed at a consistent RPM, increasing vacuum performance by 30% and reducing fuel consumption to only 1.5 gallons per operating hour.

(*As tested by GM installation)

High Heat: up to 240°F working water temperatures for exceptional cleaning results

Powerful Performance: 365 CFM for fast drying time, adjustable pressure up to 1200 PSI for upholstery, carpet and hard surface cleaning

Fuel Efficiency: the Electronic Throttle Module (ETM) regulates the van RPM reducing fuel consumption

Compact Design: 25" is all that's required, leaving the rest of your cargo space available for other equipment

Safety Features: Park Break Sensor, High Temperature Shutdown, Waste Tank Full Shutdown and Security Hose Ports to keep your equipment safe while you work

Warranty: 5 Year Extend-A-Care Warranty protects your investment for years to come

Engine: Direct drive system powered by host vehicle engine

Blower: Roots 45 Whispair DSL (dual splash lubricant, no grease fittings), 365 CFM, oil site lines & lube port on front panel

Filter System: Twin 2.5" stainless steel blower protection filters, lift out lint basket

Pump: 5CP Cat Pump, clutch activated, 1200 PSI factory setting adjustable down to 50 PSI

Heat Method: Dual reverse flow heat exchangers, 200°F water temperature up to 240°F with included Heat Max P.T.I. post heat system

Van radiator fluid travels one direction, high pressure water travels the other direction through the first heater providing up to 205 degrees F water. The Roots 47 blower produces up to 240 degree exhaust air heat once you start cleaning. The PTI heat exchanger is used to adsorb this additional heat.

Gauge Package: vacuum gauge, hour meter, blower speed tachometer, water pressure gauge, water temperature gauge

Waste Tank: 100 gallon powder coated 3/16 marine aluminum with 'Flow Max' unrestricted airflow design, sloped floor for easy draining, 120 gallon optional

Drain System: 2" drain valve

>

Or optional additional external auto drain
CleanCo Truckmount 237-035 Automatic Drain, Discharge System External
C.A.D. w/ Panel Mount

Freshwater Tank: optional 125 gallon Aqua Reel tank

Optional
CleanCo 225-310 Fresh Water tank 125 gal Aqua Tank Reel And Dual 250 ft
Electric Hose Reel

Optional
CleanCo 225-206 Truckmount 120 Gallon Fresh Water Tank with Chemical
Storage Rack

Dimensions: 58" L x 25" W x 37" H
Weight: 656 lbs

Precision Balanced PTO Drive Shaft
100 Gallon Waste Tank
Roots 45 Whispair DSL Vacuum Blower
5CP Clutch Activated Cat Pump
Dual Coolant Heat Exchangers (205°F max)
Dual Solutions Connections
Dual 2" Vacuum Connections
Dual Speed Settings (carpet & upholstery)
Quick Release Control Panel: gauge package, pressure & temperature
adjustment, chemical flow meter, pre-wired auto drain, pump & blower oil site
lines, blower lube port
Titanium 2" Truckmount Carpet Wand
100 ft x 2" Vacuum Hose
100 ft High Temperature Solution Hose
Chemical Jug & Holder
Interior Light Package
Park Break Sensor

>

Security Hose Port
High Temperature Shutdown
Waste Tank Full Shutdown
5 Year Extend-A-Care Warranty
Operation & Maintenance Manual
Embroidered Cleanco Jacket

Owners manual
Van Specifications for Compact Direct Drives
Chev and GMC Cargo Vans

2012-2018 Chev/GMC Savana Van 4.8 L, and 6.0 L V8 Gas

NOTE: Not Compatible with Passenger Vans

Cleanco does not recommend installing Compact Direct Drive PTO units in a van that has excessive wear and tear or is older than specified above.

Cleanco requires a minimum van specification of $\frac{3}{4}$ ton for Compact Direct Drive PTO systems without the transfer of fresh water, 6.0 L 1 ton with the transfer of fresh water.

It is recommended that prior to the purchase of a van, the customer review the specifications of the van with an authorized Cleanco Distributor or contact Cleanco directly.

Optional Van \$39,000 to \$40,000

Van and equipment package can be a single payment to the finance company.

Availability: This product was added to our catalog on Wednesday 06 December, 2017