

>



Model Number: C348A

Mytee C348A, Ametek Lamb Vacuum Motor Blower, 6.6 Inches, W/ 2in inlet tube CONE, 240 volts, Tangential, 2 Stage 1 Speed

Manufacturer: Ametek-Lamb

Mytee C348A Ametek 6.6" vacuum motor with 2" inlet tube / cone 240 Volts

147" water lift

7.5 Amp 240 Volts

Longer bearing and carbon brush life.

This motor is becoming recognized as 43 % better performance replacement for the old 116103-00 7.2" vac motors.

Currently, they are being used in

Mytee LX Carpet Extractors. with (2) 6.6" motors.

- Mytee only sells this model as a replacement for EXISTING MACHINES ONLY.
- NO RETROFITS, OR AFTER MARKET SALES ALLOWED BY FACTORY.
- Model and Serial number required or MFG will cancel order.

\*\*\* Add the Model and Serial number of the machine you are repairing to the comments page at time of check out \*\*\*

More water lift at the carpet. Mytee's new Hybrid Vacuum Motor outperforms where it matters most.

Water lift is measured with a gauge with the airline sealed. But sealed air doesn't clean- most vacuums are designed to work at a 3/4" to 7/8" orifice. That is approximately the opening of a wand slot. We want to measure the water lift at the carpet, not at the machine. To accomplish this, Mytee put a vacuum gauge on the wand head to measure the water lift at the carpet. Mytee's revolutionary new hybrid vacuum motor has an increase of almost 30% at an unbelievable lift at the carpet of 113". While base specifications may seem lower, the in-use specifications are in reality much higher than those of comparable motors. This high efficiency is due to the unique winding of the motor and special fan configuration.

Specifications on single vacuum motor:

173 CFM at 2" orifice

147" base water lift

113" water lift when sealed to the carpet

7.5 amp draw @ 240V

6.6 diameter

Specifications for two motors in air series:

225 CFM (SteamBrite test 216 CFM)

180" base water lift @ zero CFM

>

113&Prime; water lift at the carpet &ndash; 20% more efficient than any other vacuum motor in its class (because it is using 20% more electricity)

7.5 amp draw per cord

Sales are final on all electrical components, including but not limited to, vacuum motors, pumps, and heaters.

Tab Mounting, Thermal Protection Manual, Insulation Class A, Ball Bearings, Ambient Temperature 40 Degrees C, Body Dia. 8.4 In., Overall Height 7 In., Mounting Brackets Aluminum, Intermittent Duty, Average Life 1500 hr., Nominal Efficiency 45 Percent Standards : UL Recognized E47185

Sales tax collected in CA and TX.

Optional

Add Vacuum Motor Lint Screen Filtration and Gasket to any vacuum motor

Gasket Vacuum Motors fits 5.7in Vacuum Motors 1/4" Thick PP43-807110  
Mytee G004A PX13

*Availability: This product was added to our catalog on Friday 03 August, 2018*