

>



Model Number: RRV4G40-VRT-PKG

AR RRV4G40-VRT-PKG, 4000 psi 4 gpm 1 Inch Shaft Gas Engine, direct Coupling Pump Package, Slap Happy

Manufacturer: Annovi Reverberi Pumps

This pump package from Annovi Reverberi with a part number of RRV4G40-VRT-PKG is rated: 4000PSI, 4.0GPM AR Direct Drive Pump with Unloader, Injector & Thermal Valve.

The Annovi Reverberi / AR North America RRV4G40-VRT-PKG pump with bolt-on unloader, chemical injector, thermal valve and garden hose inlet connector. RRV D Version with F24 flange series pumps are designed to direct drive on gasoline engines ranging from 8 -13 HP. Intended use for heavy tasks; this triplex plunger pump features the latest in design and technology. Life tested over 2,000 hours at maximum performance.

Features

- Latest in design and technology
- New crankcase style
- High strength forged brass manifold for long term use
- NEW ceramic plungers, thicker wall to help prevent thermal shock
- Stainless steel valves
- Side mount valve seat o-rings
- High quality high pressure seals
- NEW low pressure seal with built in scraper
- Two piece piston guides
- NEW connecting rod with 12% more load surface
- Large side cover sight glass
- Oversized bearings
- Rear cover oil drain
- Forged, precision ground crankshaft

Specifications:

- Max. Volume: 4.0 GPM
- Max. Discharge Pressure: 4,000 PSI
- Max. Pump Speed: 3,400 RPM
- Shaft Diameter: 1" Hollow
- Max. Horsepower Requirements: 14.55 GHP
- Max. Fluid Temp.: 140° F.
- Oil capacity: 13.35 oz

>

- Unloader Inlet: 3/4" GH (garden hose)
- Unloader Outlet: 3/8" Female
- Weight: 21.10 lb.

What comes with the package:

- RRV4G40D-F24 pump
- VRT3-310 EZ Start adjustable pressure unloader
- 1/2" Black bypass hose
- Thermal relief valve
- Brass Line Strainer w/ Cone Filter, GH Inlet
- 3/8" QC brass socket
- 3/8" QC steel plug

Availability: This product was added to our catalog on Tuesday 17 December, 2019