Ametek Lamb Mytee C351, 6.6 Inch Vacuum Motor Blower, 120 volts LX Tangential, 2 Stage 1 Speed



Model Number: C351

Ametek Lamb Mytee C351, 6.6 Inch Vacuum Motor Blower, 120 volts LX Tangential, 2 Stage 1 Speed

Manufacturer: Ametek-Lamb

Mytee C351 Ametek 6.6" vacuum motor

Low Amp LX™ vacuum motor for LTD12-LX Speedster®
Draws 10 amps.

This is a drop in replacement for the old 116103 7.2" model with the same exact mounting but will have a way more increased performance for a little more amps.
147" water lift
15 Amp 120 Volts
Longer bearing and carbon brush life.
This motor is becoming recognized as 43 % better
performance replacement for the old 116103-00 7.2" vac motors.
Currently, they are being used in
Mytee LX Carpet Extractors. with (2) 6.6" motors.

More water lift at the carpet. Mytee’s new Hybrid Vacuum Motor outperforms where it matters most.
Water lift is measured with a gauge with the airline sealed. But sealed air doesn’t clean- most vacuums are designed to work at a 3/4” to 7/8” orifice. That is approximately the opening of a wand slot. We want to measure than the water lift at the carpet, not at the machine. To accomplish this, Mytee put a vacuum gauge on the wand head to measure the water lift at the carpet. Mytee’s revolutionary new hybrid vacuum motor has an increase of almost 30% at an unbelievable lift at the carpet of 113”. While base specifications may seem lower, the in-use specifications are in reality much higher than those of comparable motors. This high efficiency is due to the unique winding of the motor and special fan configuration.
Specifications on single vacuum motor:

CFM at 2″ orifice @ zero inches of lift
″ base water lift @ zero cfm
″ water lift when sealed with hose and carpet cleaning wand
15 amp max draw
6.6 diameter

Sales are final on all electrical components, including but not limited to, vacuum

Ametek Lamb Mytee C351, 6.6 Inch Vacuum Motor Blower, 120 volts LX Tangential, 2 Stage 1 Speed

motors, pumps, and heaters.

Tab Mounting,Thermal Protection Manual,Insulation Class A,Ball Bearings,Ambient Temperature 40 Degrees C,Body Dia. 8.4 In.,Overall Height 7 In.,Mounting Brackets Aluminum,Intermittent Duty,Average Life 1500 hr.,Nominal Efficiency 45 Percent Standards : UL Recognized E47185

Sales tax collected in CA and TX.

Optional

Add Vacuum Motor Lint Screen Filtration and Gasket to any vacuum motor

Gasket Vacuum Motors fits 5.7in Vacuum Motors 1/4" Thick PP43-807110 Mytee G004A PX13

Availability: This product was added to our catalog on Tuesday 03 August, 2021

Steambrite Supply