

>



Model Number: 967910303

Husqvarna 967910303, DM 400 Electric Core Drill Motor Rig, 4.3 Hp 120Volts 14 in Max, Freight Included, GTIN 805544252553

Manufacturer: Husqvarna Equipment

Husqvarna 967910303 DM 400 Electric Core Drill Motor Rig 4.3 Hp 120Volts 14 in Max Freight Included

Description

DM 400 is a powerful and sturdy electric core drill for medium to heavy core drilling where reliability and high productivity is needed. Recommended diameter 55-350 mm. With aluminium motor housing to withstand tough handling and a carrying handle for ergonomic usage and additional impact protection of the drill motor. Equipped with Embedded Connectivity, an enhanced version of Husqvarna Fleet Services™ for data analytics and insights into the health of the machine. Suitable for water evacuation, ventilation, angle drilling , stitch drilling and when you need to cut close to corners.

Features

- Sturdy and durable
- Ergonomic
- Optimised RPM's
- Embedded Connectivity
- Quick connection
- Quick-release washer
- Functional design
- The LED indicator shows the load of the machine, allowing the operator to always drill at maximum pressure, for best performance.
- The machine uses pulsation to warn you of an approaching overload. This increases productivity and extends product life.
- Reliable gearbox
- Used with starting a hole, speed is reduced by half using the Smart Start® button, which reduces vibration.
- Drilling holes in stepless adjustable angles.
- Drilling for installation of stair rails, fences, etc.
- Drilling horizontally.

>

- Drilling multiple holes next to each other to make openings.
- Drilling upwards and downwards.
- Drilling for water evacuation.

Compare to current or past OEM associations:

DM400 Drill Motor

DM 400

967910303

967 91 03-03

GTIN 805544252553

Technical Specifications

Motor

Frequency

50-60 Hz

Voltage

100-120 V

Rated input power

4.29 hp

Drilling Equipment

Drill bit diameter with stand, max

14 in

Recommended drill bit diameter, min

2 in

Specifications

Water pressure, max

>

43.5 psi

Spindle Outer Thread
1 1/4" 7 UNC

Transmission

Number of gearbox speeds
3

Dimensions

Water connector
G 1 / 4"

Weight
34.2 lbs

Product size L x W x H
21.5 in x 5.5 in x 7.3 in

Sound and Noise

Sound Power Level, Measured
110 dB(A)

Sound Pressure Level at Operators Ear
92 dB(A)

Sound power level, guaranteed (LWA)
112 dB(A)

Warranty

>

Factory Warranty
1 Year

Documents
Product Sheet
Manual
Parts List

Availability: This product was added to our catalog on Tuesday 27 September, 2022