

>



Model Number: 970445602

Husqvarna 970445602, DM 430 Electric Core Drill Motor Rig, 120v 4.2Hp 18IN Max, Freight Included, GTIN 805544252584

Manufacturer: Husqvarna Equipment

Husqvarna 970445602 DM 430 Electric Core Drill Motor Rig 120v 4.2 hp 18 in Max Freight Included

#### Description

DM 430 is a powerful and sturdy electric core drill for medium to heavy core drilling where reliability and high productivity is needed, especially with large diameter core bits. Recommended diameter 100-450 mm. With aluminium motor housing to withstand tough handling and a carrying handle for ergonomic usage and additional impact protection of the drill motor. Equipped with Embedded Connectivity, an enhanced version of Husqvarna Fleet Services® for data analytics and insights into the health of the machine. Suitable for water evacuation, ventilation, angle drilling, stitch drilling and when you need cut close to corners.

#### Features

- Sturdy and durable
- Ergonomic
- Optimised RPM's
- Embedded Connectivity
- Quick connection
- Quick-release washer
- Functional design
- The LED indicator shows the load of the machine, allowing the operator to always drill at maximum pressure, for best performance.
- The machine uses pulsation to warn you of an approaching overload. This increases productivity and extends product life.
- Reliable gearbox
- Used with starting a hole, speed is reduced by half using the Smart Start® button, which reduces vibration.
- Drilling holes in stepless adjustable angles.
- Drilling for installation of stair rails, fences, etc.
- Drilling horizontally.

>

- Drilling multiple holes next to each other to make openings.
- Drilling upwards and downwards.
- Drilling for water evacuation.

Compare to current or past OEM associations:

DM430 Drill Motor

DM 430

970445602

GTIN 805544252584

970 44 56-02

Technical Specifications

Motor

Frequency

50-60 Hz

Voltage

100-120 V

Rated input power

4.29 hp

Drilling Equipment

Drill bit diameter with stand, max

18 in

Recommended drill bit diameter, min

4 in

Specifications

Water pressure, max

>

43.5 psi

Spindle Outer Thread  
1 1/4" 7 UNC

Transmission

Number of gearbox speeds  
3

Dimensions

Water connector  
G 1 / 4"

Weight  
34.2 lbs

Product size L x W x H  
23 in x 5.5 in x 7.3 in


Sound and Noise

Sound Power Level, Measured  
110 dB(A)

Sound Pressure Level at Operators Ear  
92 dB(A)

Sound power level, guaranteed (LWA)  
112 dB(A)

Warranty



Factory Warranty  
1 Year

Documents  
Product Sheet  
Manual  
Parts List



*Availability: This product was added to our catalog on Sunday 17 September, 2023*

